



ECOCONDENS CRYSTAL - 80



ECOCONDENS CRYSTAL 80 wall mounted gas condensing boilers are intended for heating large objects such as: multifamily buildings, boarding houses or office buildings. Boilers can work as independent units as well as in a cascade system. The modern control system used in the boiler allows to combine up to 6 boilers into a cascade without the need for an additional cascade manager and to achieve a total output of up to 480 kW.

- innovative heat exchanger design makes the boilers small in size in relation to their power output,
- high efficiency circulation pump ($EEL \leq 0,23$),
- venting of the boiler is carried out by an air-vent mounted on the exchanger,
- electronically controlled modulating fan which ensures low energy consumption,
- burner with a wide range of modulation which ensures low NOx emissions (5th Class),
- two preinstalled adapters with measuring points: $\varnothing 100$ air and $\varnothing 100$ exhaust gas,
- NTC sensor of hydraulic coupling on the boiler equipment,
- Open-Therm communication protocol,
- works with domestic hot water cylinders with a coil output of min. 25 kW,
- high efficiency circulation pump with a lifting height of 8m; boiler version with pump of 12m lifting height available on request.

Accessories

CR11011



TERMET ST-292 V2



TERMET ST-292 V3



OUTSIDE TEMPERATURE SENSOR



parameters

Value

Thermal power (at temp. 80/60°C)	17,0 - 80,0 kW
Thermal power (at temp. 50/30°C)	19,0 - 88,0 kW
Heat load	18,0 - 82,0 kW
Efficiency of the boiler at nominal load and average boiler water temperature of 70°C	97,0 %
Efficiency of the boiler at partial load and return water temperature of 30°C	107,0 %
Efficiency η_4	87 %
Efficiency η_1	95 %
Max water pressure	4 bar
Standard adjustable temperature	20 - 80 °C
Pump head at 0 flow	0,8 bar
Sound power level LWA	62 dB
Emission of nitrogen dioxide	≤ 50 mg/kWh
Emission class of nitrogen dioxide (NOx)	5
Max. amount of condensate (natural gas)	12 l/h
Type and supply voltage	$\sim 230 \pm 10\%$ / 50Hz V
Protection degree	IPX4D
Connection to the chimney duct	2 x $\varnothing 100$
Heating water and gas connection	G 5/4 -- G 1 inch
Dimensions	810 x 540 x 545 mm
Weight	84 kg
Exchanger material	stainless steel