



ZWU 200/N Plus



ZWU-200/N tank is the most modern solution to supplying with domestic hot water. It is designed for single-family houses, multi-family residential buildings and buildings of public use with few water supply points.

- compatible with wall-hung system boilers:
 - UNICO ELEGANCE-13
 - UNICO ELEGANCE-24
 - UNICO ELEGANCE-29
 - UNICO ELEGANCE-13 turbo
 - UNICO ELEGANCE-21 turbo
 - UNICO ELEGANCE-24 turbo
 - UNICO ELEGANCE-29 turbo
- compatible with condensing system boilers:
 - ECOCONDENS CRYSTAL II-20
 - ECOCONDENS CRYSTAL II-25
 - ECOCONDENS CRYSTAL II-35
 - ECOCONDENS GOLD-20
 - ECOCONDENS GOLD-25
 - ECOCONDENS GOLD-35
 - ECOCONDENS SILVER PLUS-20
 - ECOCONDENS SILVER PLUS-25
 - ECOCONDENS SILVER PLUS-35
 - ECOCONDENS CRYSTAL-50
- housing made of sheet steel covered with white powder paint
- tank made of sheet steel, covered with special ceramic enamel from the inside, which protects against corrosion and provides high quality of heating water
- pre-installed magnesium anode which protects against corrosion
- safety valve included in boiler's equipment

Parametry

Wartość

Energy efficiency class of water heating	A
Cold water connection	G 1 inch
Hot water connection	G 1 inch
Cylinder capacity	200 dm ³
Cylinder surface	1,65 m ²
DHW efficiency (60/10/45°C)	710 dm ³ /h
Daily heat loss	0,81 kWh/24h
Heating water demand	2,2 m ³ /h
Resistance of water flow in the coil	70 mbar
Operating parameters of the tank	max. pressure pr = 0,6 MPa; working temp. tm = 90°C
Cylinder weight without water	65 kg
Cylinder height	1200 mm
Cylinder diameter	720 mm
Heating water connection	G 3/4 inch
Circulation connection	G 3/4 inch